

HOROLITH FL**Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : HOROLITH FL

UFI : 2PDN-6WR3-QF0G-F61E

Product code : 117653E

Use of the Substance/Mixture : Cleaning product

Substance type: : Mixture

For professional users only.

Product dilution information : 0.0 % - 1.5 %

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Process cleaner. Cleaning In place (CIP) process

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Limited
Forest Park
Mullingar Industrial Estate, Mullingar Co. Westmeath Ireland +353
1 276 3500
infoireland@ecolab.com

Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+353 (0)1 276 3500
ccs@ecolab.com

1.4 Emergency telephone number

Poison Information Centre telephone number : Poisons Information: For information or to report a poisoning incident contact The National Poisons Information Centre (01 8092166)

Date of Compilation/Revision : 07.05.2025
Version : 2.3

Section: 2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

HOROLITH FL

Classification (REGULATION (EC) No 1272/2008)

Product AS SOLD

Corrosive to metals, Category 1	H290
Acute toxicity, Category 3	H331
Skin corrosion, Category 1	H314
Serious eye damage, Category 1	H318

Product AT USE DILUTION

Skin corrosion, Category 1	H314
Serious eye damage, Category 1	H318
The classification of this product is based only on its extreme pH value (in accordance with current European legislation).	

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Product AS SOLD

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H290 May be corrosive to metals.
H314 Causes severe skin burns and eye damage.
H331 Toxic if inhaled.

Supplemental Hazard Statements : EUH071 Corrosive to the respiratory tract.

Precautionary Statements : **Prevention:**
P260 Do not breathe spray.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

Hazardous components which must be listed on the label:

Nitric acid

Phosphoric acid

Product AT USE DILUTION

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H314 Causes severe skin burns and eye damage.

HOROLITH FL

Precautionary Statements	: Prevention: P280	Wear protective gloves/ eye protection/ face protection.
	Response: P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
	P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P310	Immediately call a POISON CENTER/doctor.

2.3 Other hazards**Product AS SOLD**

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Product AT USE DILUTION

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Product AS SOLD****Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
Nitric acid	7697-37-2 231-714-2 01-2119487297-23	Nota B Oxidizing liquids Category 2; H272 Acute toxicity Category 3; H331 Skin corrosion Category 1A; H314 Serious eye damage Category 1; H318 Skin corrosion Category 1A H314 >= 20 % Skin corrosion Category 1B H314 5 - < 20 % Oxidizing liquids Category 3 H272 65 - < 99 % Oxidizing liquids Category 2 H272 >= 99 % Skin corrosion/irritation Category 2 1 - < 5 %	>= 30 - < 50
Phosphoric acid	7664-38-2 231-633-2 01-2119485924-24	Nota B Skin corrosion Sub-category 1B; H314 Serious eye damage Category 1; H318 Corrosive to metals Category 1; H290 Acute toxicity Category 4; H302 Serious eye damage/eye irritation Category 1 > 25 - 100 % Serious eye damage/eye irritation Category 2 10 - 25 % Skin corrosion/irritation Category 1B > 25 - 100 % Skin corrosion/irritation Category 2	>= 3 - < 5

HOROLITH FL

10 - 25 %

Product AT USE DILUTION
Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
Nitric acid	7697-37-2 231-714-2 01-2119487297-23	Oxidizing liquids Category 2; H272 Acute toxicity Category 3; H331 Skin corrosion Category 1A; H314 Serious eye damage Category 1; H318 Skin corrosion Category 1A H314 >= 20 % Skin corrosion Category 1B H314 5 - < 20 % Oxidizing liquids Category 3 H272 65 - < 99 % Oxidizing liquids Category 2 H272 >= 99 % Skin corrosion/irritation Category 2 1 - < 5 %	>= 0.1 - < 1

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES**4.1 Description of first aid measures****Product AS SOLD**

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention immediately.

Product AT USE DILUTION

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.
- In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.
- If swallowed : Rinse mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention immediately.

HOROLITH FL

if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

Product AS SOLD

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Not flammable or combustible.

Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:
Not applicable.

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Product AS SOLD

Advice for non-emergency personnel : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Product AT USE DILUTION

Advice for non-emergency personnel : Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Avoid inhalation, ingestion and contact with skin and

HOROLITH FL

	eyes. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.
Advice for emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Product AS SOLD

Environmental precautions : Do not allow contact with soil, surface or ground water.

Product AT USE DILUTION

Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

Product AS SOLD

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

Product AT USE DILUTION

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Product AS SOLD

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. Do not mix with bleach or other chlorinated products – will cause chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing

HOROLITH FL

of the eyes and body in case of contact or splash hazard.

Product AT USE DILUTION

Advice on safe handling : Do not ingest. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation. Wash hands thoroughly after handling. Do not breathe spray, vapour. Do not mix with bleach or other chlorinated products – will cause chlorine gas. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

7.2 Conditions for safe storage, including any incompatibilities**Product AS SOLD**

Requirements for storage areas and containers : Protect from frost, heat and sunlight. Store at room temperature in the original container. Keep away from strong bases. Absorb spillage to prevent material damage. Keep out of reach of children. Keep container tightly closed. Keep only in original packaging. Store in suitable labeled containers.

Storage temperature : -20 °C to 40 °C

Packaging material : Suitable material: Plastic material

Unsuitable material: Mild steel, Aluminium

Product AT USE DILUTION

Requirements for storage areas and containers : Protect from frost, heat and sunlight. Store at room temperature in the original container. Keep away from strong bases. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

7.3 Specific end uses**Product AS SOLD**

Specific use(s) : Process cleaner. Cleaning In place (CIP) process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters****Product AS SOLD****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Nitric acid	7697-37-2	OELV - 15 min (STEL)	1 ppm 2.6 mg/m ³	IR_OEL
Phosphoric acid	7664-38-2	OELV - 8 hrs (TWA)	1 mg/m ³	IR_OEL
		OELV - 15 min (STEL)	2 mg/m ³	IR_OEL

DNEL

Nitric acid	:	End Use: Workers
-------------	---	------------------

HOROLITH FL

		Exposure routes: Inhalation Potential health effects: Short-term - local Value: 2.6 mg/m³ End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1.3 mg/m³
Urea	:	End Use: Workers Exposure routes: Dermal Potential health effects: Acute systemic effects Value: 580 mg/kg bw/day End Use: Workers Exposure routes: Inhalation Potential health effects: Acute systemic effects Value: 292 mg/m³ End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 580 mg/kg bw/day End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 292 mg/m³ End Use: Consumers Exposure routes: Dermal Potential health effects: Acute systemic effects Value: 580 mg/kg bw/day End Use: Consumers Exposure routes: Inhalation Potential health effects: Acute systemic effects Value: 125 mg/m³ End Use: Consumers Exposure routes: Inhalation Potential health effects: Acute systemic effects Value: 42 mg/kg bw/day End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 580 mg/kg bw/day End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 125 mg/m³ End Use: Consumers Exposure routes: Oral Potential health effects: Long-term systemic effects Value: 42 mg/kg bw/day

HOROLITH FL**PNEC**

Urea	:	Fresh water Value: 0.47 mg/l
		Marine water Value: 0.47 mg/l

8.2 Exposure controls**Product AS SOLD****Appropriate engineering controls**

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Eye/face protection (EN 166) : Safety goggles
Face-shield

Hand protection (EN 374) : Recommended preventive skin protection
Gloves
Nitrile rubber
butyl-rubber
Breakthrough time: 1 – 4 hours
Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advice).
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Skin and body protection (EN 14605) : Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes

Respiratory protection (EN 143, 14387) : When respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization, consider the use of certified respiratory protection equipment meeting EU requirements (89/656/EEC, (EU) 2016/425), or equivalent, with filter type:A-P

Product AT USE DILUTION**Appropriate engineering controls**

Engineering measures : Effective exhaust ventilation system. Maintain air concentrations below occupational exposure standards.

Individual protection measures

HOROLITH FL

Hygiene measures	: Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.
Eye/face protection (EN 166)	: Safety goggles Face-shield
Hand protection (EN 374)	: Recommended preventive skin protection Gloves Nitrile rubber butyl-rubber Breakthrough time: 1 – 4 hours Minimum thickness for butyl-rubber 0.7 mm for nitrile rubber 0.4 mm or equivalent (please refer to the gloves manufacturer/distributor for advise). Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Skin and body protection (EN 14605)	: Personal protective equipment comprising: suitable protective gloves, safety goggles and protective clothing including appropriate safety shoes
Respiratory protection (EN 143, 14387)	: None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES**9.1 Information on basic physical and chemical properties**

	Product AS SOLD	Product AT USE DILUTION
Physical state	: liquid	liquid
Colour	: colourless	colourless
Odour	: pungent	not significant
pH	: 0.9 - 1.1, 100 %	0.0 - 0.5
Particle characteristics		
Assessment	: not applicable	not applicable
Particle size	: not applicable	not applicable
Particle Size Distribution	: not applicable	not applicable
Dustiness	: not applicable	not applicable
Specific surface area	: not applicable	not applicable
Surface charge/Zeta	: not applicable	not applicable

HOROLITH FL

potential

Shape	: not applicable	not applicable
Crystallinity	: not applicable	not applicable
Surface treatment /Coatings	: not applicable	not applicable
Flash point	: Not applicable.	
Odour Threshold	: Not applicable and/or not determined for the mixture	
Melting point/freezing point	: Not applicable and/or not determined for the mixture	
Boiling point, initial boiling point and boiling range	: > 100 °C	
Evaporation rate	: Not applicable and/or not determined for the mixture	
Flammability	: Not applicable and/or not determined for the mixture	
Upper explosion limit	: Not applicable and/or not determined for the mixture	
Lower explosion limit	: Not applicable and/or not determined for the mixture	
Vapour pressure	: Not applicable and/or not determined for the mixture	
Relative vapour density	: Not applicable and/or not determined for the mixture	
Density and / or relative density	: 1.25 - 1.35	
Water solubility	: soluble	
Solubility in other solvents	: Not applicable and/or not determined for the mixture	
Partition coefficient: n-octanol/water (log value)	: Not applicable and/or not determined for the mixture	
Auto-ignition temperature	: Not applicable and/or not determined for the mixture	
Thermal decomposition	: Not applicable and/or not determined for the mixture	
Viscosity, kinematic	: Not applicable and/or not determined for the mixture	
Explosive properties	: Not applicable and/or not determined for the mixture	
Oxidizing properties	: Yes	

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY**Product AS SOLD****10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

HOROLITH FL

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Bases

Mild steel
Aluminium

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:
Not applicable.

In the event of fire, see Section 5

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product AS SOLD

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity	: Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity	: 4 h Acute toxicity estimate : 5.81 mg/l Test atmosphere: vapour
Acute dermal toxicity	: There is no data available for this product.
Skin corrosion/irritation	: There is no data available for this product.
Serious eye damage/eye irritation	: There is no data available for this product.
Respiratory or skin sensitization	: There is no data available for this product.
Carcinogenicity	: There is no data available for this product.
Reproductive effects	: There is no data available for this product.
Germ cell mutagenicity	: There is no data available for this product.
Teratogenicity	: There is no data available for this product.
STOT - single exposure	: There is no data available for this product.
STOT - repeated exposure	: There is no data available for this product.
Aspiration toxicity	: There is no data available for this product.

Components

HOROLITH FL

Acute oral toxicity : Phosphoric acid LD50 rat: > 300 mg/kg

Components

Acute inhalation toxicity : Nitric acid 4 h LC50 : 2.65 mg/l
Test atmosphere: vapour

Potential Health Effects**Product AS SOLD**

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : Toxic if inhaled. May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Product AT USE DILUTION

Eyes : Causes serious eye damage.

Skin : Causes severe skin burns.

Ingestion : Causes digestive tract burns.

Inhalation : May cause nose, throat, and lung irritation.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure**Product AS SOLD**

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

Product AT USE DILUTION

Eye contact : Redness, Pain, Corrosion

Skin contact : Redness, Pain, Corrosion

Ingestion : Corrosion, Abdominal pain

Inhalation : Respiratory irritation, Cough

11.2 Information on other hazards

Endocrine disrupting properties : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

Further information : no data available

HOROLITH FL

Section: 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Product AS SOLD

Environmental Effects : This product has no known ecotoxicological effects.

Product AT USE DILUTION

Environmental Effects : This product has no known ecotoxicological effects.

**Product AS SOLD
Product**

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to fish : Nitric acid
96 h LC50: 72 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : Phosphoric acid
48 h EC50 Daphnia magna (Water flea): > 100 mg/l

Components

Toxicity to algae : Phosphoric acid
72 h EC50 Desmodesmus subspicatus (green algae): > 100 mg/l

12.2 Persistence and degradability

Product

no data available

Components

Biodegradability : Nitric acid
Result: Not applicable - inorganic

Phosphoric acid
Result: Not applicable - inorganic

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be

HOROLITH FL

either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher

12.7 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product AS SOLD

- | | | |
|-----------------------------------|---|---|
| Product | : | Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations. Dispose of wastes in an approved waste disposal facility. |
| Contaminated packaging | : | Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations. |
| Guidance for Waste Code selection | : | Inorganic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations. |

Product AT USE DILUTION

- | | | |
|------------------------|---|---|
| Product | : | Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of contents/container in accordance with local regulations. Dispose of wastes in an approved waste disposal facility. |
| Contaminated packaging | : | Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations. |

Section: 14. TRANSPORT INFORMATION

Product AS SOLD

HOROLITH FL

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

14.1 UN number or ID number : 2031
 14.2 UN proper shipping name : NITRIC ACID
 14.3 Transport hazard class(es) : 8
 14.4 Packing group : II
 14.5 Environmental hazards : No
 14.6 Special precautions for user : None

Air transport (IATA)

14.1 UN number or ID number : 2031
 14.2 UN proper shipping name : Nitric acid
 14.3 Transport hazard class(es) : 8
 14.4 Packing group : II
 14.5 Environmental hazards : No
 14.6 Special precautions for user : None

Sea transport (IMDG/IMO)

14.1 UN number or ID number : 2031
 14.2 UN proper shipping name : NITRIC ACID
 14.3 Transport hazard class(es) : 8
 14.4 Packing group : II
 14.5 Environmental hazards : No
 14.6 Special precautions for user : None
 14.7 Maritime transport in bulk according to IMO instruments : Not applicable.

Section: 15. REGULATORY INFORMATION**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****Regulation (EU) 2019/1148 on the marketing and use of explosives precursors**

This product is regulated (containing reportable or/and restricted substances) by Regulation (EU) 2019/1148 (explosives precursors): all suspicious transactions, significant disappearances and thefts should be reported to the relevant national contact point.

Seveso III: Directive : ACUTE TOXIC H2
 2012/18/EU of the European Lower tier : 50 t
 Parliament and of the Council Upper tier : 200 t
 on the control of major-
 accident hazards involving
 dangerous substances.

Candidate List of Substances : Not applicable.

HOROLITH FL

of Very High Concern for
Authorisation

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : Safety, Health and Welfare at Work Act, 2005
European Communities (Classification, Packaging, Labelling and
Notification of Dangerous Preparations) Regulations 1995. (S.I.
272 of 1995) as amended

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION**Procedure used to derive the classification according to REGULATION (EC) No 1272/2008**

Classification	Justification
Corrosive to metals 1, H290	Based on product data or assessment
Acute toxicity 3, H331	Calculation method
Skin corrosion 1, H314	Based on product data or assessment
Serious eye damage 1, H318	Based on product data or assessment

Full text of H-Statements

H272 May intensify fire; oxidiser.
H290 May be corrosive to metals.
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H331 Toxic if inhaled.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC)

HOROLITH FL

No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios**Exposure Scenario: Process cleaner. Cleaning In place (CIP) process**

Life Cycle Stage : Use at industrial sites

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC4** Industrial use of processing aids in processes and products, not becoming part of articles

Daily amount per site : 50 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC8b** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

HOROLITH FL

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC1** Use in closed process, no likelihood of exposure

Exposure duration : 480 min

Operational conditions and
risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8